



# PLATUNA® ALLOY 1

### PLATINUM RUTHENIUM ELECTROLYTE



#### Extraordinarily Abrasion-Resistant Coatings – Saving Platinum

PLATUNA® Alloy 1 is used for depositing smooth, ultra-bright and extraordinarily abrasion-resistant platinum-ruthenium alloy coatings. The acidic electrolyte is used for decorative applications and guarantees light, white layers - crack-free up to 1  $\mu$ m.

PLATUNA® Alloy 1 works across a wide operating range and reaches an excellent covering speed. It is used for rack operation.



#### **Advantages**

- Acidic platinum alloy electrolyte saves expensive platinum
- · Light, white and ultra-bright coatings
- · For decorative applications
- · Extraordinarily abrasion-resistant
- · Wide operating range
- Up to 1 μm layer thickness (crack-free)
- · The coatings are RoHS compliant
- · Suitable for racks

#### **Applications**

- Jewellery
- · Writing implements
- Watches
- · Spectacle frames
- Accessories

# PLATUNA® ALLOY 1

# PLATINUM RUTHENIUM ELECTROLYTE




## **TECHNICAL SPECIFICATIONS**

Electrolyte characteristics	
Electrolyte type	Strongly acidic
Metal content	1.0 (0.8 - 1.2) g/l Pt 1.0 (0.8 - 1.2) g/l Ru
pH value	< 1
Operating temperature	35 (30 - 40) °C
Current density range	2.0 (0.5 - 5.0) A/dm <sup>2</sup>
Plating speed	Approx. 0.08 μm/ min at 2.0 A/dm²
Anode material	MMO (type PLATINODE® 187 SO)

Coating characteristics	
Coating	Platinum-ruthenium
Alloy composition	75 weight % Pt 25 weight % Ru
Colour of deposit	White
Brightness	Bright
Hardness of deposit HV 0.015 (Vickers) approx. values	Not measurable, Approx. 500 HV
Max. coating thickness	1.0 µm
Density of the coating	Approx. 19.16 g/cm³

#### Bosch-Weinmann Wear Test



Umicore Galvanotechnik GmbH

73525 Schwaebisch Gmuend (Germany)

Technical Support: Phone +49 7171 607-305
Sales Department: Phone +49 7171 607-204



